

**Standards of the storage enterprise to be established within the scopes of the Project on “Co-financing of Processing and Storage Enterprises” (component of “Co-financing for storage enterprises”)**

**Building of storage enterprise and adjacent territory**

1. Storage chambers of the permanent structure or/and construction intended for storage enterprise should be wrapped with polyurethane sandwich panels or polyurethane sandwich panels should be attached to metal construction (polystyrene may be also applied).
2. Storage enterprise should be designed in accordance with the basic requirements of HACCP (hazard analysis and critical control points) system;
3. Additional rain roofing should be attached to the construction / permanent structure;
4. It should be possible to work with loaded vehicles in the adjacent area of the buildings;
5. Following should be provided in storage enterprise: toilet accommodations, disinfection barriers, showers and cloakrooms separately for men and women;
6. Storage enterprise should be supplied with water and electricity sources;
7. The floor of the storage enterprise should be made of concrete with processed and polished surface. Storage enterprise should be divided into chambers and provide the possibility for storage of products under the project;
8. Adjacent territory of the storage enterprise should be fenced;
9. Fenced territory of the storage enterprise partially intended for roadway of the trucks, should be covered with asphalt layer or concrete;
10. Land plot chosen for storage enterprise construction should have the access for truck vehicle.

**Equipment for storage enterprise**

1. Individual adjustment for temperature regime and humidity of each chamber should be available at the enterprise in order to ensure the food safety and retention of stable quality;
2. Storage enterprise should be equipped with scaled with capacity no less than 500 kg;
3. Refrigerator warehouse of storage facility should be equipped with appropriate aggregates in accordance with the needs, ensuring the necessary temperature regime;
4. Dry warehouse of storage enterprise should be equipped with ventilation system, ensuring the ventilation of facility, air flow movement and excluding the overheating of products;
5. Aggregates to be purchased for the storage enterprise should not use the ozone-depleting substances, in particular HCFC22 and should use alternative and natural refrigerants, such as hydrocarbons, natural gas and Freon.